

PRIOR ART STATUS REPORT CONSTRUCTION,

유


PROGRESS CHECKING OPERATIONS,


DISASTER SITE, ETC.

DOBUDGEL DEDECO

PRIOR ART

PRIOR ART








FIG. 5

(Pos[O].x, Pos[O].y)
(Pos[1].x, Pos[1].y)
(HALFWAY OMITTED) (Pos[n].x, Pos[n].y)
(1 OSTIII.X, 1 OSTIII.Y)
(HALFWAY OMITTED)
(Pos[N-1].x, Pos[N-1].y)
i i





FIG. 7

OSSUBSE SECTION




SHADED FRAMES INDICATE THAT SUFFICIENT QUALITIES ARE NOT GIVEN DUE TO NARROW-BAND Δ_t is sampling frequency, in case of NTSC standard 1/29.97 Hz = approximately 33.37 msec


NOTE

3

NOTE

IMAGE TRANSMISSION






DIRICIPAL DADED


NOTE

 Δt is sampling frequency. In case of NTSC standard 1/29.97 Hz = approximately 33.37 msec shaded frames indicate that sufficient quality is not given due to narrow-band


NOTE

IMAGE TRANSMISSION





SCREEN OBTAINED BY REDUCING AND SYNTHESIZING 4 FRAMES



SCREEN OBTAINED BY REDUCING AND SYNTHESIZING 9 FRAMES

FIG. 13A

FIG. 13B


ossanse, cecano


NOTE NOTE NOTE 1)

IMAGE TRANSMISSION

SHADED FRAMES INDICATE THAT SUFFICIENT QUALITY IS NOT GIVEN DUE TO NARROW - BAND

At IS SAMPLING FREQUENCY. IN CASE OF NTSC STANDARD 1/29.97 Hz = APPROXIMATELY 33.37 msec









FIG. 17




COCHOCK- OMOROD

NOTE


IMAGE


TRANSMISSION


SHADED FRAMES INDICATE THAT SUFFICIENT QUALITY IS NOT GIVEN DUE TO NARROW - BAND



D ဖ







Donnoar Jacono